

DH-DVR0404HD-A

4 Channel HD-SDI 1080P 1U Standalone DVR



Features

- > Up to 4 channel HD-SDI video 1080p realtime live view
- > H.264 dual-stream video compression
- > Max 100/120fps@1080p
- > HDMI / VGA / TV synchronous video output
- > 4 channel synchronous realtime playback, GRID interface & smart search
- > 3D intelligent positioning with Dahua PTZ dome camera
- > Support 2 SATA HDDs up to 8TB.
- > Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

DH-DVR0404HD-A

Technical Specifications


Model		DH-DVR0404HD-A
System		
Main Processor	Dual-core embedded processor	
Operating System	Embedded LINUX	
Video		
Input	4 channel, BNC	
Standard	1080P(25/30) / 720P(25/30,50/60)	
Audio		
Input	4 channel, BNC	
Output	1 channel, BNC	
Two-way Talk	1 channel Input, 1 channel Output, BNC	
Display		
Interface	1 HDMI, 1 VGA, 1 TV, BNC	
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768	
Display Split	1/4	
Privacy Masking	4 rectangular zones (each camera)	
OSD	Camera title, time, video loss, camera lock, motion detection, recording	
Recording		
Video/Audio Compression	H.264 / G.711	
Image Resolution	1080P(1920×1080), 720P(1280×720) D1(704×576 / 704×480), CIF(352×288 / 352×240)	
Record Rate	Main stream	Max 100/120fps@1080p
	Extra stream	D1/CIF(25/30fps)
Bit Rate	256~8096Kb/s	
Recording Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop	
Recording Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec	
Video Detection & Alarm		
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen tips	
Motion Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank	
Alarm Input	4 channel	
Relay Output	3 channel	
Playback & Backup		
Sync Playback	1/2/4	
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search	
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup	

DH-DVR0404HD-A

	selection, Digital zoom(any size)
Backup Mode	USB Device / Internal SATA burner/ Network
Network	
Ethernet	RJ-45 port (10/100M/1000M)
Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, Alarm Server
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Storage	
Internal HDD	2 SATA ports, up to 8TB
External HDD	1 eSATA port (Max 4 SATA HDDs), up to 16TB
Auxiliary Interface	
USB Interface	2 ports (1 Rear), USB2.0
RS232	1 port, For PC communication & Keyboard
RS485	1 port, For PTZ control
General	
Power Supply	DC12V/ 5A
Power Consumption	15W(without HDD)
Working Environment	-10 ~ +55°C / 10~90%RH / 86~106kpa
Dimension(W×D×H)	1U, 375mm×285mm×45mm
Weight	2.35KG(without HDD)

DH-DVR0404HD-A

System Connection



Dahua Technology Co., Ltd. 1187BinAn Road, Binjiang District, Hangzhou, China

Tel: 66956096-09126017817-09107616575

email:imensazaa@gmail.com

www.irandahua.com